



Style 2960

(Vegetable Fiber)
Sheet Gasketing

Style 2960 Vegetable Fiber Sheet Service

Meets latest revisions of these specifications: HHP 96 Type I; MIL-G-12803 (ORD) Type III Class 2 Group 1; ASTM D 1170-62; P3313 (Ships).

For service with compressed air, coal tar gasoline, hot and cold water, inert gases and oil. Style 2960 effectively resists the solvent action of petroleum products. It remains tough and durable through a long service life but is pliable and compressible for secure installation. Style 2960 is composed of vegetable fibers impregnated with a compound that seals the fibers to fluids.

How to Order

Specify: style number, size and quantity

Thickness		Approx. Weight Per Roll (Width: 36": 0.9144M)	
Inches	Millimeters	Lbs./sq yd	Kgs./sq.M.
.010	0.25	.50	0.27
.015 (1/64)	0.4	.65	0.35
.02	0.5	.75	0.41
.031 (1/32)	0.8	1.20	0.65
.047 (3/64)	1.2	1.75	0.95
.062 (1/16)	1.6	2.25	1.22
.093 (3/32)	2.4	3.50	1.90
.125 (1/8)	3.2	4.75	2.58

Available in 25 yard (22.86 M) rolls.

Distributed by

A Greene, Tweed Company
Denton Industrial Park
25 Engerman Ave., Denton, MD 21629
Phone: +1.410.479.2244, Fax: +1.410.479.0836
E-mail: info@palmettopackings.com
Website: www.palmettopackings.com

Product data is based upon our experience and knowledge of typical applications and should be used to determine approximate service compatibility.

All trademarks are property of their respective owners.
Printed in USA ©2014 Palmetto®
05/14-GT DS-US-PI-180